

7200 GROUNDMASTER

PRODUCT SPECIFICATIONS

TORO

Specifications

Engine	Kubota, 3-cylinder, liquid-cooled Diesel. Power: 24.8hp (18.6 kW) gross, at rated speed of 3,000rpm. Torque peak: 52.7 ft. lbs. (71.5 Nm) @ 2,200 rpm. Displacement: 1,123cc. High idle: 3200 rpm. Remote mounted 5" Donaldson air cleaner. Fuel filter/water separator. EPA Tier IV Final Compliant.
Fuel Capacity	43.5 Litre Diesel
Ground Speed	Forward 0-12.5 mph (0-20 km/h), variable. Reverse 0-8.5 mph (0-13.7 km/h), variable.
Height Rops Up	183 cm
Overall Length	246.4 cm
Overall Width	157.5 cm Base Deck
Ground Speed	Forward 0-20 km/hr Reverse 0-13.7 km/hr
Shipping Weight	214 kg
Width of Cut	62" deck rear discharge



DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is: for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.