AP600F WHEEL PAVER

PRODUCT SPECIFICATIONS

Engine - powertrain CAT C4.4 ACERT Engine Engine Speed - maximum / minimum Eco-mode Screed Heating - Standard width (quiet) Screed Heating - W/extensions (quick) Speed Ranges Paving	129 kW 175 hp (M) / 173 hp (I) 2,200 / 1,000 rpm 1,650 rpm 1,300 rpm 1,300 to 2,200 rpm
Eco-mode Screed Heating - Standard width (quiet) Screed Heating - W/extensions (quick) Speed Ranges	1,650 rpm 1,300 rpm 1,300 to 2,200 rpm 76 mpm 250 fpm
Screed Heating - Standard width (quiet) Screed Heating - W/extensions (quick) Speed Ranges	1,300 rpm 1,300 to 2,200 rpm 76 mpm 250 fpm
Screed Heating - W/extensions (quick) Speed Ranges	1,300 to 2,200 rpm 76 mpm 250 fpm
Speed Ranges	76 mpm 250 fpm
Paving	
	05
With Tamper-bar Screed	25 mpm 82 fpm
Travel	16 km/hr
Italian Rode Homologation	14.9 km/hr
Weights	
APF600F Paver Only - Shipping	13,558 kg
APF600F Paver Only - Operating	13,845 kg
Operating Weight - Includes full fuel tank and 75 kg (16	65 lb) operator.
Capacities	
Maximum Throughput Capacity	1,300 tonnes/h / 1,433 tph
Hopper Capacity - With tunnels	7.1 m³ / 250 ft³
Fuel Tank	278 L / 73 gal
DEF (Urea) Capacity - CAT 4.4 engine only	19.1 L
Engine Oil - CAT 4.4 engine	13.5 L
CAT 7.1 engine	15.5 L
Cooling System - CAT C4.4 engine	31 L
CAT 7.1 engine	37 L
Hydraulic Tank	219 L
Screed Specifications	
Paving Range w/SE50 V, SE50 VT	2.55 - 5.0 m
Paving Range w/SE60 V	3.0 - 6.0 m
Maximum Paving Width w/SE50 V	6.5m
Maximum Paving Width w/SE50 VT	8.0m
Maximum Paving Width w/SE60 V	7.65m
Maximum Paving Depth	305mm
Extender Height Range	-20mm to +50mm

Crown Range SE50 V	-4% to +10% (total)
Crown Range SE50 VT	-2% to +5% (per side)
Crown Range SE60 V	-4% to +10% (total)
Extender Slope Range SE50 V, SE60 V	-3% to +10%
Extender Slope Range SE50 VT	-3% to +2%
Fuel Burn	
Low	7.6 - 11.4 Litres per hour
Medium	11.4 - 17.0 Litres per hour
High	17.0 - 22.7 Litres per hour



