

DCA-150ESK POWER GENERATOR | 125KVA

PRODUCT SPECIFICATIONS

DENYO

Alternator	
Frequency	50 Hz
Output Continuous/Standby	125 / 138 kVA
Rotating Speed	1,500 RPM
Number of phases	Three Phase 4 wire
Rated Voltage	380 / 440
Power Factor	0.8
Voltage Regulation %	+0.5
Excitation	Brushless, Rotating Exciter (with A.V.R.)
Insulation	Class F
Engine	
Make and Model	KOMATSU SAA6D102E-2-D
Type	Inlined, Direct injected, Turbocharged, After cooled
Output Rating	153 / 1,500 PS/rpm 113 / 1,500 KW/min-1
Number of Cylinders - Bore X Stroke	6-102 x 120 mm
Piston Displacement	5.880 L
Fuel	Diesel
Fuel Consumption	20.6 L/H
Lube Oil Sump Cap	22 L
Coolant Capacity	28.4 L
Battery Capacity	95E41RX2
Fuel Tank Capacity	250 L
Dimensions	
Length	3000 mm
Width	1080 mm
Height	1500 mm
Dry Weight	2120 kg



DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.