

DCA-15ESK-DA POWER GENERATOR | 12.5KVA

PRODUCT SPECIFICATIONS

DENYO

Alternator	
Frequency	50 Hz
Output Continuous/Standby	12.5 / 13.5 kVA
Rotating Speed	1,500 RPM
Number of phases	Three Phase 4 wire
Rated Voltage	380 / 440
Power Factor	0.8
Voltage Regulation %	+1.5
Excitation	Brushless, Rotating Exciter (with A.V.R.)
Insulation	Class F
Engine	
Make and Model	Kubota 1403-EB
Type	Inlined, Swirl Chambered
Output Rating	16.9 / 1,500 PS/rmp 12.4 / 1,500 KW/min-1
Number of Cylinders-Bore X Stroke	3-80 x 92.4 mm
Piston Displacement	1.393 L
Fuel	Diesel
Fuel Consumption	2.4 L/H
Lube Oil Sump Cap	5.6 L
Coolant Capacity	6.4 L
Battery Capacity	12 – 60x1pc
Fuel Tank Capacity	62 L
Dimensions	
Length	1,390 mm
Width	650 mm
Height	900 mm
Dry Weight	516 kg



DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is: for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.