

# DCA-75SP1 POWER GENERATOR | 65KVA

## PRODUCT SPECIFICATIONS

DENYO

Alternator	
Frequency	50 Hz
Output Continuous/Standby	65 / 68.3 kVA
Rotating Speed	1,500 RPM
Number of phases	Three Phase 4 wire
Rated Voltage	380 / 440
Power Factor	0.8
Voltage Regulation %	+0.5
Excitation	Brushless, Rotating Exciter (with A.V.R.)
Insulation	Class F
Engine	
Make and Model	ISUZU A-6BG1
Type	Inlined, Direct injected
Output Rating	80 / 1,500 PS/rpm 58.8 / 1,500 KW/min-1
Number of Cylinders - Bore X Stroke	6 - 105 x 125 mm
Piston Displacement	6.494 L
Fuel	Diesel
Fuel Consumption	10.8 L/H
Lube Oil Sump Cap	19.3 L
Coolant Capacity	22.9 L
Battery Capacity	95E41RX2
Fuel Tank Capacity	155 L
Dimensions	
Length	2,630 mm
Width	1,000 mm
Height	1,300 mm
Dry Weight	1,590 kg



DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is: for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.