

E2850 MOBILE TRANSFER VEHICLE

PRODUCT SPECIFICATIONS

WEILER



Powertrain

CAT C9 Tier III Engine w/ 300 hp

4-Wheel Drive

Shift-on-the-fly 3-speed hydrostatic drive

194 fpm Working Speed

10 mph Transport Speed

Differential Lock

2-Wheel Steering Standard

Optional rear steer w/ 14' turning radius

High-torque, direct-drive motors

Loop Flush Return System

Specifications

Weight: 74,500 lb

Length: 52' 3"

Width: 119"

Height: 16'

Truck Hopper Width: 113"

Storage Capacity: 25 Tons

Elevator Capacity: 1000 tph

Elevator Slat Width: 58"

Conveyor Capacity: 600 tph

Conveyor Slat Width: 30"

Transport Speed: 10 mph

Working Speed: 194 fpm

Turning Radius: 30' std, 14' w/ Rear Steer

Tyres: 21.00" - 25", 28 ply

Fuel Tank Capacity: 150 gal

Hydraulic Tank Capacity: 100 gal

Fuel Burn

Low 5.6 Litres per hour

Medium 24.41 Litres per hour

High 35.09 Litres per hour

DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is: for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.