

RTX1250 TRENCHER

PRODUCT SPECIFICATIONS

VERMEER

Engine	
Model	Cummins QSB4.5 TAA
Horse Power @ 2300 rpm	125 hp / 93.2 kW
Horse Power @ 2500 rpm	120 hp / 89.5 kW
Horse Power @ 2500 rpm (net)	110 hp / 82 kW
Torque (max @ 1500 rpm)	350 ft-lb / 474.5 Nm
Displacement	275 cu in / 4.5 L
Number of Cylinders	4
Fuel Type	Diesel
Trencher	
Weight (without boom)	984.3 kg / 2170 lb
Max Transport Length	221 cm
Trencher Depth Range	0 - 182.9 cm
Trencher Width Range	15.2 - 45.7 cm
Extension Bracket Weight - With rubber quad tracks	161 kg
Rockwheel	
Weight - no teeth, 6' (15.2cm) segments, 40' (101.6 cm) wheel	2,893.9 kg
Max Transport Length	3.4 m
Max Cutting Depth	101.6cm
Max Cutting Width	350 mm
Drive Type	Hydrostic
Discharge Chute Position	Dual
Ground Clearance - In Transport	50.8 cm



DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is: for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.