


12,500 RIGID WATER TRUCK | 12,500L

PRODUCT SPECIFICATIONS

HINO

Engine	
Model	Hino A09C-TT
Maximum Output (ISO Net)	221 kW (300 PS) at 2,100 RPM
Maximum Output (JIS Gross)	224 kW (305 PS)
Maximum Torque (ISO Net)	1079 Nm (110 kgf/m) at 1,100 RPM
Maximum Torque (JIS Gross)	1098 Nm (112 kgf/m)
Maximum Engine speed	2100 RPM
Engine Compliance	ADR 80/03
Type	Diesel, turbocharged and intercooled, six-cylinder in-line, overhead camshaft and water-cooled
Combustion System	Direct injection with EGR
Bore and Stroke	112 x 150 mm
Piston Displacement	8.886 L
Compression Ratio	17.0:1
Engine Oil Capacity	28.7 L
Coolant Capacity	33.5 L
Fuel Injection Pump	Electronic control common-rail type
Intake System	Stack-type air intake
Air Cleaner	Dual paper elements
Air Compressor	Single cylinder, water-cooled
Bore and Stroke	85 x 60 mm
Fan Clutch	Equipped
Exhaust	Horizontal outlet with DPR
Emission Control System	EGR and DPR meeting ADR 80/03 using EURO V Std
Fuel Burn	
Low	2.6 - 11.7 Litres per hour
Medium	11.7 - 17.4 Litres per hour
High	17.4 - 20.1 Litres per hour



DISCLAIMER: This Product Specification Sheet was produced 01/2020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is for general information only and does not purport to be comprehensive, current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profits resulting from use of or misuse of the general information provided in this document.