
CB7 TANDEM VIBRATORY ROLLER | 9T

PRODUCT SPECIFICATIONS

Туре	Double Drum	
Specifications		
Engine Model	CAT C2.4B	
Gross Power Tier 4 Interim - Stage IIIB	75 kW (100 hp)	
Operating Weight	8,190 kg (max 8,940 kg)	
Static Linear Load	26.9 kg/cm	
Amplitude - Solid drum VT1	0.25mm (low) - 0.64mm (high)	
Frequency	53.3 Hz	
Centrifugal Force - High	76.9 kN	
- Low	30.2 kN	
Speed Range (km/ h)	0-12 km/h	
Water Tank (I)	742 L	
Fuel Burn		
Low	6.8 Litres per hour	
Medium	8.3 Litres per hour	
High	10.2 Litres per hour	



170 mm
16 mm
1108 mm





DISCLAMER: This Product Specification Sheet was produced 0110200. Every effort has been made to ensure that the content is accurate, however the contents are subject to change Information contained in this Specification Sheet is: for general information only and dees not purport to be comprehensive; current only at the time it is pleaded in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Ezyquip Hire makes no warranty express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages to iss of profits resulting from use of or misuse of the general information provided in this document.