

## **GW 750-2 VIBRATORY PNEUMATIC ROLLER | 9T**

**PRODUCT SPECIFICATIONS** 

Туре	Multi-Tyre Roller
Masses	
Operating Mass (incl. ROPS)	9,280 kg
Compaction	
Compaction Width	1,950 mm
Tyre size x Number of tyres (Front / Rear)	14 / 17 - 20 - 12 PR (3/4)
Tyre Pressure	441 kPa
Centrifugal Force (Front 1 / 2 / 3 / 4)	6 / 19 / 32 / 45 kN
Centrifugal Force (Rear 1 / 2 / 3 / 4)	8 / 25 / 42 / 58 kN
Frequency	40 Hz
Gradeability	38% / 20°
Traction	
Speed 1 / 2 / 3 (km/h)	5 / 7 / 12 km/h
Engine	
Manufacturer / Model	ISUZU "DD-4BG1T" Tier2 : equivalent
Туре	Water cooled turbo Diesel, 4 cycle, 4 cylinder inline
Displacement	2.999 L
Fuel Tank Capacity	130 L
Rated Power	92 kW (123hp)
Electrical System	24 V





**USCLAMER**: This Product Specification Sheet was produced 1012020. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is for general information only and des not purport to be comprehensive; current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsbeever. Ezyquip Hire makes no warranty express or implied, induding without limitation any warranty of merchantability or fitness for any particular purpose. Ezyquip Hire shall not be liable for any special, incidental, or consequential damages or loss of profils resulting from use of or misuse of the general information provide nor make any recommendation upon which this document.

