## **BROOM**PRODUCT SPECIFICATIONS

## **BS3000 HST Broom Features**

The Kubota B3000 is compact and light enough to be towed on a tandem trailer behind a ute or light crew cab but with sweeping capabilities you would normally expect from something three times the size.

- 30HP B3000 with three range HST transmission
- ROPS or air-conditioned factory cabin models available
- · Remote mounted pre-cleaner on ROPS or cabin
- · Flashing beacon with dash mounted switch
- Front mounted 1.75m five section hydraulic driven broom
- Independent PTO mounted broom pump and filtered 60 litre rear mounted reservoir for maximum cooling
- · Clutchless engagement of broom drive
- · Hydraulic lift and angle via cab or platform mounted joy stick
- Electro hydraulic anti-drop valve prevents storage damage to brushes
- Unique spring activated contour following lateral pivot on broom ensures substantially reduced coning and even brush wear
- · Operator can easily replace brush sections in the field in just minutes.



B3150 HDCC Broom Specifications	
Engine	Kubota 4 cylinder Diesel V1505-E3-D26BH-A,1498cc 31hp @ 2,500rpm 3 range pedal operated HST hydrostatic transmission
Broom	Clutchless engagement of broom drive. Filtered rear mounted 60 litre hyd. res. for max cooling. Spring activated contour following lateral pivot ensures even brush pressure and reduced coning.
Overall Broom Width	2.13 m
Sweeping Width (max)	1.75 m
Sweeping Width (angle min)	1.66 m
Broom Diameter	530 mm
Weight (tractor/broom)	1,560kg



