
## TS160-2 PNEUMATIC ROLLER | 3T

**PRODUCT SPECIFICATIONS** 

Туре	Multi-Tyre Roller
Masses	
Operating Mass (incl. Cab)	2,900 kg
Traction	
Speed Range (km/ h)	0 - 15
Gradeability	47% (25°)
Front Wheels / Rear Wheels	4, Drive / 3, Guide
Tyre Size	9.5/65-15-6PR (OR) smooth tread
Overlap	83 mm
Sprinkler Tank Capacity	185 L
Engine	
Manufacturer / Model	Kubota "D1105-K2A" Diesel Engine
Туре	Water cooled, 4-cycle
Output	14.6 kW / 2,300 min
Fuel Tank Capacity	36 L



DISCLAMER: This Product Specification Sheet was produced 101202. Every effort has been made to ensure that the content is accurate, however the contents are subject to change. Information contained in this Specification Sheet is for general information only and does not purport to be comprehensive; current only at the time it is placed in this document compiled from manufacturer and industry sources; and not intended to provide nor make any recommendation upon which you should rely for any purpose whatsoever. Expujie Hire makes no warranty express or implied, including without limitation any warranty of merchantability or filtness for any particular purpose. Expujie Hire shall not be liable for any special, incidental, or consequential damages or loss of profils resulting from use of or misuse of the general information provide in this document.

